

# Indac Wallace Seals



The INDAC Wallace Seal has been specifically designed to make the fitting of overflow pipes and down pipes to polyethylene tanks simple and reliable.

Simply drill hole, fit the Wallace Seal and insert pipe. The INDAC Wallace Seal operates to a depth of 15mm, suits curved and flat surfaces.

Unique multiple lips ensure a high integrity seal.

Easy to install, you only require the right sized hole saw and drill.

The INDAC Wallace Seal creates a semi-flexible joint between pipe and tank.



*Range of sizes for all applications*



*Quick and simple to install*

CODE	SUITABLE FOR	HOLE SAW SIZE	PIPE DIAM mm: (min-max)
XWS25PP	25mm Pressure Pipe	44mm	33.4 - 33.7
XWS32SW	32mm Drain Waste & Vent	44mm	36.2 - 36.5
XWS40SW	40mm Drain Waste & Vent	52mm	42.8 - 43.1
XWS50SW	50mm Drain Waste & Vent	65mm	55.7 - 56.0
XWS65SW	65mm Drain Waste & Vent	76mm	68.7 - 69.1
XWS80SW	80mm Drain Waste & Vent	89mm	82.3 - 82.7
XWS90SW	90mm Stormwater	98mm	90.0 - 90.3
XWS100SW	100mm Stormwater	121mm	110.0 - 110.4
XWS150SW	150mm Drain Waste & Vent	168mm	160.0 - 160.5



**INDAC**

INNOVATIVE DESIGN AND CONSTRUCTION

FREEPHONE

0800 803 888

www.indac.nz

Email info@indac.co.nz